

FEP

TIPO TYPE	Ø INTERNO / INSIDE Ø	Ø ESTERNO / OUTSIDE Ø	ESERCIZIO (20°C) SERVICE (68°F)	SCOPPIO (20°C) BURST (68°F)	RAGGIO MIN. CURV MIN. BEND RADIUS	PESI / WEIGHTS
	(mm)	(mm)	(bar)	(bar)	(mm)	(gr/mt)
TNFEP0250X0400	2,5	4	22	66	25	17
TNFEP0200X0400	2	4	30	90	20	21
TNFEP0320X0635	3,2	6,35	31	94	25	52
TNFEP0400X0600	4	6	19	57	35	35
TNFEP0400X0635	4	6,35	22	65	35	42
TNFEP0476X0635	4,76	6,35	14	41	35	31
TNFEP0300X0600	3	6	31	93	30	47
TNFEP0600X0800	6	8	14	42	40	48
TNFEP0635X0950	6,35	9,5	19	57	40	86
TNFEP0800X1000	8	10	10	30	60	62
TNFEP0950X1270	9,5	12,7	14	41	85	123
TNFEP1000X1200	10	12	9	27	85	76
TNFEP1200X1400	12	14	7	21	150	90
TNFEP1400X1600	14	16	6	18	200	104
TNFEP1560X1900	15,6	19	9	28	180	203
TNFEP1600X1800	16	18	5	15	350	117
TNFEP1600X1900	16	19	8	24	300	181
TNFEP1800X2000	18	20	14	41	85	123
TNFEP2200X2500	22	25	4	12	400	131
TNFEP2500X2800	25	28	5	16	500	275

DISPONIBILI VERSIONI SPIRALI. AVAILABLE SPIRALS VERSIONS.

PFA

TIPO TYPE	Ø INTERNO / INSIDE Ø	Ø ESTERNO / OUTSIDE Ø	ESERCIZIO (20°C) SERVICE (68°F)	SCOPPIO (20°C) BURST (68°F)	RAGGIO MIN. CURV MIN. BEND RADIUS	PESI / WEIGHTS
	(mm)	(mm)	(bar)	(bar)	(mm)	(gr/mt)
TNPFA0250X0400	2,5	4	20	60	25	17
TNPFA0200X0400	2	4	28	84	20	21
TNPFA0400X0600	4	6	17	51	35	35
TNPFA0300X0600	3	6	30	90	30	47
TNPFA0600X0800	6	8	14	42	65	48
TNPFA0800X1000	8	10	10	30	80	62
TNPFA1000X1200	10	12	9	27	90	76

DISPONIBILI VERSIONI SPIRALI. AVAILABLE SPIRALS VERSIONS.

PVDF

TIPO TYPE	Ø INTERNO / INSIDE Ø	Ø ESTERNO / OUTSIDE Ø	ESERCIZIO (20°C) SERVICE (68°F)	SCOPPIO (20°C) BURST (68°F)	RAGGIO MIN. CURV MIN. BEND RADIUS	PESI / WEIGHTS
	(mm)	(mm)	(bar)	(bar)	(mm)	(gr/mt)
TNPVDF0250X0400	2,5	4	37	111	25	14
TNPVDF0200X0400	2	4	53	159	20	17
TNPVDF0400X0600	4	6	34	102	35	28
TNPVDF0300X0600	3	6	53	159	30	38
TNPVDF0600X0800	6	8	24	72	40	39
TNPVDF0800X1000	8	10	18	54	60	50
TNPVDF1000X1200	10	12	15	45	85	61

DISPONIBILI VERSIONI SPIRALI. AVAILABLE SPIRALS VERSIONS.